

## SPECIFICATIONS

Properties	Typical Values	Test Procedures/Method
Electrostatic Decay	0.01 seconds at 72°F and 11.8% R.H.	FED-STD-101, Method 4046
Surface Resistance	10E6 - 10E8 ohms/sq. after 11 days at 68°F and 12% R.H. for surface. 10E3 - 10E4 ohms/sq. for buried shielding layer	ASTM D257
Surface Resistance, Low R.H. Cut-off	4% R.H.	Rockwell International Test Report of December 20, 1991
High-Voltage Discharge Resistance	Failure rate 0/5 (no oxide damage in five consecutive tests)	Rockwell International Test Report of December 20, 1991
Static Shielding	99.9% attenuation at 10kV; 99.6% attenuation at 30kV	EIA 541, appendix E, capacitive probe test
Charged Device Model (CDM) Safety	RTG >10E7 ohms at 86% R.H. or less	Rockwell International Test Report of December 20, 1991
Current-Carrying Hazard	10E3 mA at 110V; 10E3 mA at 220V	ESD from A to Z
Corrosivity	Contains 1-3 ppm reducible sulfur	FED-STD-101, Method 3005 for reducible sulfur
Antistat Transfer	No transfer	Rockwell International Test Report of January 8, 1992
Water & Isopropyl Alcohol Extraction Tests for Antistat Permanence	Surface resistance 10E8 - 10E9 ohms/square at 74°F and 36% R.H.	Rockwell International Test Report of January 8, 1992
Sloughing Test	Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test.	ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load
	No conductive particles abrased from surface	Rockwell International Test Report of January 8, 1992
Recyclability	Complete recyclability of package	Rockwell International Test Report of January 8, 1992
Biodegradability	Biodegradation in or on moist soil	
Volume Conductivity	Conductivity from wall to wall as well as across surface to assure permanence of the antistatic property	Rockwell International Test Report of January 8, 1992 Made in
Shelf Life	Indefinite	
	TEK-TRA	YS

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 ProtektivePak.com



## Features

- Trays that can stack and nest together for improved use of space
- Great container for Kanban

Item No.	Size I.D L x W x D (mm)	
37750	457 X 289 X 44	
37751	578 X 441 X 70	

in America

DATE:

11/06

DRAWING NUMBER

37750.E