



Adjustable Wrist Band


BAND

- Designed to be used with a Coiled Cord with a one megohm current limiting resistor meeting the EN 61340-5-1 Personnel Grounding requirements tested per ANSI/ESD S1.1.
- Surface-Inside: 80 threads Acrylonitrile-Copper Sulfide dye composition fibre for inner conductive material
- Surface-Outside: Polyester fibre
- Band Resistance: 80-90 ohm/inch
- 360° Wrist Contact

PLASTIC PLATE & LATCH

- Plastic Plate: Polycarbonate
- Latch: Polycarbonate

METAL BASE #304 Stainless Steel



Metal Base

360° Constant Wrist Contact

“A wrist strap system consists of three elements: the person, the wrist cord and a wrist band. To ensure that the resistance to ground of personnel is within the specifications, it is important to measure the entire system (i.e. from the person's body to the end of the ground cord).

“Wrist straps typically consist of a wrist band which makes contact with the wearer's skin. The wrist band is then attached to a grounding cord which is connected to the ESD ground reference.”

“The wrist band is a flexible, form-fitting device designed to make a reliable continuous connection to a person's wrist”. [CLC TR 61340-5-2 2008 User guide Wrist Strap clauses 4.5.2, 4.7.2.2, and 4.7.2.2.1]

Item	Description
60062	4mm stud version
60061	10mm stud version
60063	4mm stud version, non-allergenic
60064	10mm stud version, non-allergenic

Unless otherwise noted tolerance is $\pm 10\%$

Specifications and procedures subject to change without notice.



Wrist Band, Elastic, Adjustable, Economy

CHARLESWATER LTD.
 UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
 CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
 PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
 INTERNET: Charleswater.co.uk

Drawing Number
 60062.E

DATE:
 October
 2010