




Clasp



Park-It Hole



Made in the
United States of America

Wrist band and Coiled Cord

- Used with [resistive loop technology continuous monitor](#), continuously verifies the proper resistance to ground of the operator

Wrist band

- Woven Silveron™ fabric infused with silver monofilament conductive fiber is comfortable and hypo-allergenic
- 4mm snaps are machined to precision profile from 300 series stainless steel for a consistent and reliable connection.
- 304 stainless steel back plate

Coiled Cord

- Coiled cord with molded 1 megohm current limiting resistor on both ground paths to protect user from shock due to inadvertent contact with line voltage
- 28 gauge wire
- 3.5mm phono plug connector
- Single (Snap-One™) snap head allows operators to quickly and easily attach and detach the cord from the wristband
- Park-it feature on Snap-One™ molded snap head provides convenient park station for cord when not in use. Simply insert phono plug into hole to allow for hanging cord at workbench.
- Custom manufactured right angle mono-plug reduces chance of accidental disconnects and provides more secure ground connection

Continuous Monitors pay for themselves improving quality, productivity, eliminating wrist strap daily testing and test result logging. Leading companies use continuous monitors as a cost effective component in satisfying some of the audit and check requirements of EN 61340-5-1.

Wrist strap testing “Where continuous monitoring is used, no additional testing is required.” [EN 61340-4-1, per A.5.2]

“The wrist band will normally be worn for several hours at a time so it needs to be comfortable while making good contact with the skin. It is a good idea to check the wrist strap every time it is applied. Constant on line monitors can be used so that any breaks will be immediately found.” [EN 61340-5-2 clause 5.2.7]
Detects the current limiting resistance built into the coiled cord, verifying the lower limit as well as the upper limit.

Per ANSI/ESD S1.1 paragraph 6.1.3 Frequency of Functional Testing “Daily [Wrist Strap] testing may be omitted if constant monitoring is used.”

Per User guide CLC/TR 61340-5-2 Wrist Strap clause 4.7.2.4.4 Test frequency “Because wrist straps have a finite life, it is important to develop a test frequency that will guarantee integrity of the system. Typical test programs recommend that wrist straps that are used daily should be tested daily. However, if the products that are being produced are of such value that a guarantee of a continuous, reliable ground is needed then continuous monitoring should be considered or even required.”

Improve wrist band contact with wrist using [Rezstore™ ESD Hand Lotion](#).

Unless otherwise noted, tolerance is ± 10%

Specifications and procedures subject to change without notice.

Dual-Wire Adjustable Wrist Strap, 4mm Snaps, 6 Ft. Right Angle Cord



CHARLESWATER LTD.
UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
PHONE: 00 44 (0) 1892-665313
INTERNET: Charleswater.co.uk

DRAWING NUMBER
63150.E

DATE:
January
2015