



### **Grounding & Cleaning**

If the material is used on top of an already properly grounded surface, <u>grounding hardware</u> may not be necessary. Where no properly grounded surface is available, <u>grounding hardware</u> is required to provide a path-to-ground. Rg compliance verification measurements must be made per EN 61340-5-1 periodically with a <u>surface resistance meter</u>.

See Tech Bulletin  $\underline{\sf TB-7000}$  for  ${\sf Reztore}^{\textcircled{R}}$  Surface & Mat Cleaner Application Instructions.

### **Limited Lifetime Warranty:**

Desco Europe warrants for one year that Statfree<sup>®</sup> matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by <u>Desco Europe Limited</u>.

#### **RoHS 2, REACH, and Conflict Minerals Statement** See the Desco Europe RoHS 2, REACH Statement:

DescoEurope.com/Desco-Europe-RoHS-REACH-Statement.pdf

See the Desco Europe Conflict Minerals Statement: Desco.Europe/pdf/Conflict-Minerals-Policy-Statement.pdf

See the Desco Europe Limited Warranty: <u>DescoEurope.com/Limited-Warranty.aspx</u>

See the Desco Europe Disclaimer: DescoEurope.com/Disclaimer.aspx

# **DESCO**EUROPE

Specifications

Standard Document EN 61340-5-1

### **Electrical Properties**

**Property** Rp-p Resistance: Rg Resistance: Test Method IEC 61340-4-1 IEC 61340-4-1 Meets Requirements of: Flooring

Value 1 x  $10^4$  to < 1 x  $10^6$  ohms 1 x  $10^4$  to < 1 x  $10^6$  ohms

Electrical Properties obtained by testing to industrial standards by an independent testing laboratory at 10 Volts and 50% relative humidity unless otherwise specified. Complete text of the test report is available upon request.

## **Physical Properties**

Material: Thickness: Colour:<sup>2</sup> Texture:<sup>2</sup> Ethylene Propylene Diene Monomer (EPDM)<sup>1</sup> 12.7 mm

Black Bubble cells

Tolerances

Width ± 6.35 mm Length ± 6.35 mm every 0.305 m of running material

<sup>1</sup>Rubber material is vulcanized and may contain sulfur. <sup>2</sup>Colour, texture, and gauge may vary between lots and mills.

For product listings, please click Here.



United States of America

Specifications and procedures subject to change without notice.

Statfree i™ Interlocking Room System, Conductive, Ergonomic, 12.7 mm

DESCO EUROPE 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY, HERTFORDSHIRE, SG6 1BE, UK PHONE: +44 (0) 1462 672005 E-MAIL: <u>Service@DescoEurope.com</u>, INTERNET: <u>DescoEurope.com</u> Drawing Number PME-i DATE: June 2020